

Product Data

ZIE R500 SAE 20w40 API CH4 / SL

Engine Oil

Description:

- It is premium high performance multi grade engine oil formulated with high quality base oil fortified with special additives to provide protection and excellent performance under varying operating conditions
- It is suitable for modern generation turbo charged and naturally aspirated engines

Features and Benefits:

- Superior detergency and excellent soot control over extended period of usage
- Helps to achieve longer engine durability even under severe operating conditions
- Possesses improved lubricant film strength for heavy load
- Reduces wear and ensures longer engine life
- Reduces oil consumption

Specifications:

Meeting the requirements of

API CH 4 /SL



Typical characteristics:

Characteristics	Test Method	Zie R500
		20w40 CH4
SAE Grade		20W40
Kinematic viscosity, cSt at 100 °C	ASTM D 445	15.82
Viscosity index, min.	ASTM D 2270	136
Flash point (COC), °C, min.	ASTM D 92	228
Pour point, °C, max.	ASTM D 97	-24
CCS Viscosity @-20°C, mPa.s	ASTM D5293	4500

The above figures are typical figures with normal production tolerance.

Health & Safety

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

All reasonable care has been taken to ensure that the information contained in this publication is accurate as at the date of printing. It should be noted however that the information above may be affected by changes occurring subsequent to the date of printing in the blend formulation or methods of application of any of the products referred to or in the requirements of any specification approval relating to any such products.